

SLA-T2880BA



SLA-T2880BA

2MP Network Bandit Barrier Lens

Key Features

- 2 Megapixel (1920 x 1080) resolution
- 2.8mm wide-angle lens provides a 107.4° FoV
- Includes an 8m cable that can be cut to length as needed
- Black color
- Supports up to 60fps@2MP
- WDR (120dB), LDC
- Adjustable height and installation options for various installation types
- cable length 8m (26 feet), can be cut to length as needed
- Requires optional XNB-6002 / PNM-9000QB main unit

SLA-T2880BA

2MP Network Bandit Barrier Lens



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.045
	BW(1/30sec, 30IRE)	0.045

Lens

Focal Length (mm)		2.8
Max. Aperture Ratio (F number)	Wide	2.0
	Tele	2.0
Angular Field of View	Horizontal	108°
	Vertical	63°
	Diagonal	122°
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

Environmental & Electrical

Operating Condition	Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
	Humidity	Less than 90% RH
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	Less than 90% RH

Mechanical

Color	Black
Material	Plastic, Metal
Product Dimensions	66.5x46x175~737mm(2.6"x1.8"x6.9~29.0"), Main Unit: 131.1x28x86mm(5.16"x1.10"x3.39"), Cable: 8m(26.2ft)
Product Weight	250~1,000g(0.55~2.205 lb), Camera Body: 245g(0.54 lb)
Supported Products	XNB-6002, PNM-9000QB, PNM-C20000QB, XNB-A8004B