



SMT-3215

32" LED monitor



Key Features

- 32 inch FHD Monitor, support up to 1920×1080 @60Hz
- Brightness 300 cd/m² (Typical), Contrast 3200:1 (Minimum) 4000:1 (Typical)
- Viewing Angle (H/V) : 178°/178°, Response Time : 20ms (Typical)
- Video Input : HDMI, DP, VGA
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-3215

32" LED monitor



Specifications

Display

Type	LED Monitor
Screen Size	32inch
Max. Resolution	1920x1080
Brightness	300 cd/m ²
Contrast Ratio	4000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	20ms
Panel Life	30,000 hours

Interface

Video	Connectors	VGA(1), HDMI(1), DP(1)
VGA	Connector	VGA
	Available Format	1920x1080@60Hz
HDMI	Connector	HDMI
	Available Format	1920x1080@60Hz
DP	Connector	DP
	Available Format	1920x1080@60Hz
Audio	Connector	Audio in(1)/out(1)
	Output Signal	Speakers : 4Ω 2.5W x 2

On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	60W

General

Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	714.0x484.2x200.8mm(28.1x19.1x7.9")
	Dimensions without Stand (WxHxD)	714.0x423.7x53.7mm(28.1x16.7x2.1")
	Weight	7.28kg(16.1lb, with stand), 5.9Kg(13lb, without stand)
	Packing Dimension (WxHxD)	790*195*503mm(31.1x7.7x19.8")
	Packing Weight	8.66Kg(19.1lb)
	Cabinet Color	Black
	VESA Mounts Interface	100x100mm